



# <u>Appendix E</u> <u>Noise Monitoring Equipment Calibration</u> <u>Certificate</u>



# CALIBRATION CERTIFICATE

Certificate Information

Date of Issue 23-May-2022

Certificate Number | MLCN221167S

**Customer Information** 

Company Name

Address

Acuity Sustainability Consulting Limited

Unit E, 12/F., Ford Glory Plaza, Nos. 37-39 Wing Hong Street, Cheung Sha Wan, Kowloon, HK

Equipment-under-Test (EUT)

Description

Sound Calibrator

Manufacturer

Scarlet Tech ST-120

Model Number Serial Number

200504747

**Equipment Number** 

Calibration Particular

Date of Calibration

23-May-2022

Calibration Equipment

4231(MLTE008) / AV200063 / 23-Jun-23

1357(MLTE190) / MLEC21/05/02 / 26-May-22

Calibration Procedure

MLCG00, MLCG15

**Calibration Conditions** 

Laboratory Temperature 23 °C ± 5 °C

EUT

Relative Humidity Stabilizing Time

 $55\% \pm 25\%$ Over 3 hours

Warm-up Time Power Supply

Not applicable Internal battery

Calibration Results

Calibration data were detailed in the continuation pages.

### Approved By & Date

K.O. Lo

23-May-2022

#### Statements

- Calibration equipment used for this calibration are traceable to national / international standards.
- The results on this Calibration Certificate only relate to the values measured at the time of the calibration and the uncertainties quoted will not include allowance for the EUT long term drift, variation with environmental changes, vibration and shock during transportation, overloading, mishandling, misuse, and the capacity of any other laboratory to repeat the measurement.
- MaxLab Calibration Centre Limited shall not be liable for any loss or damage resulting from the use of the EUT.
- The copy of this Certificate is owned by MaxLab Calibration Centre Limited. No part of this Certificate may be reproduced without the prior written approval of MaxLab Calibration Centre Limited.

Page 1 of 2



Certificate No. MLCN221167S

Calibration Data						
EUT Setting	Standard Reading	EUT Error from Setting	Calibration Uncertainty			
94 dB	95.3 dB	1.3 dB	0.15 dB			
114 dB	116.0 dB	2.0 dB	0.15 dB			

- END -

Calibrated By:

Date:

Dan

23-May-22

Checked By:

K.O. Lo

Date:

23-May-22

Page 2 of 2



# Certificate of Calibration

for

Description:

Sound Level Meter

Manufacturer:

Scarlet Tech

Type No.:

ST11D (Serial No.: 820250)

Microphone:

BSWA 231 (Serial No.:590497)

# Submitted by:

Customer:

Acuity Sustainability Consulting Limited

Address:

Unit E, 12/F., Ford Glory Plaza,

Nos. 37-39 Wing Hong Street,

Cheung Sha Wan, Kowloon, Hong Kong

Upon receipt for calibration, the instrument was found to be:

**☑** Within (31.5Hz – 4kHz)

☐ Outside

the allowable tolerance.

The test equipment used for calibration are traceable to National Standards via:

- The Government of The Hong Kong Special Administrative Region Standard & Calibration Laboratory

Date of receipt: 05 October 2022

Date of calibration: 07 October 2022

Date of NEXT calibration: 06 October 2023

Certified by:

Mr. Ng Yan Wa Laboratory Manager

Date of issue: 7 October 2022

Certificate No.: APJ22-083-CC001

Page 1 of 3



# 1. Calibration Precaution:

- The unit-under-test (UUT) was allowed to stabilize in the laboratory for over 24 hours, and switched on to warm up for over 10 minutes before the commencement of the test.
- The results presented are the mean of 3 measurements at each calibration point.

#### 2. Calibration Conditions:

Air Temperature:

23.3 °C

Air Pressure:

1005 hPa

Relative Humidity:

57.6 %

# 3. Calibration Equipment:

Type

Serial No.

Calibration Report Number

Traceable to

**Multifunction Calibrator** 

B&K 4226

2288467

AV220061

**HOKLAS** 

#### 4. Calibration Results

Sound Pressure Level

Reference Sound Pressure Level

Setting of Unit-under-test (UUT)		Applied value		UUT Reading,	IEC 61672 Class 1		
Range, dB	Freq. W	eighting/	Time Weighting	Level, dB	Frequency, Hz	dB	Specification, dB
43-138	dBA	SPL	Fast	94	1000	94.3	±0.4

#### Linearity

Sett	ing of U	nit-under-t	est (UUT)	Applied value		UUT Reading,	IEC 61672 Class 1
Range, dB	Freq.	Weighting	Time Weighting	Level, dB	Frequency, Hz	dB	Specification, dB
				94		93.8	Ref
43-138	dBA	SPL	Fast	104	1000	104.2	±0.3
				114		114.3	±0.3

# Time Weighting

Setting of Unit-under-test (UUT)		Applied value		UUT Reading,	IEC 61672 Class 1			
Range, dB	Freq. W	eighting	Time Weighting	Level, dB	Frequency, Hz	dB	Specification, dB	
43-138	JD A	SPL	Fast	0.4	1000	93.8	Ref	
43-138	dBA	SPL	Slow	94	94 100	1000	94.3	±0.3

Certificate No.: APJ22-083-CC001

(A+A) \*L

Page 2 of 3

Frequency Response

#### A-weighting

Setting of Unit-under-test (UUT)		Applied value		UUT Reading,	IEC 61672 Class 1			
Range, dB	Freq. W	eighting	Time Weighting	Level, dB	Frequency, Hz	dB	Specification, dB	
					31.5	56.2	-39.4 ±2.0	
					63	68.6	-26.2 ±1.5	
43-138 dBA SPL	Fast	94	125	78.3	-16.1 ±1.5			
			250	85.8	-8.6 ±1.4			
			500	91.1	-3.2 ±1.4			
	*			1000	94.3	Ref		
			2000	94.9	+1.2 ±1.6			
14						4000	93.5	$+1.0\pm1.6$

# 5. Calibration Results Applied

The results apply to the particular unit-under-test only. All calibration points are within manufacture's specification as IEC 61672 Class 1.

Uncertainties of Applied Value:

94 dB	31.5 Hz	± 0.10
	63 Hz	± 0.15
	125 Hz	± 0.05
	250 Hz	± 0.10
	500 Hz	± 0.10
	1000 Hz	± 0.05
	2000 Hz	± 0.05
	4000 Hz	± 0.05
104 dB	1000 Hz	± 0.05
114 dB	1000 Hz	± 0.05

The uncertainties are evaluated for a 95% confidence level.

#### Note:

The values given in this certification only related to the values measured at the time of the calibration and any uncertainties quoted will not allow for the equipment long-term drift, variations with environmental changes, vibration and shock during transportation, overloading, mis-handling, or the capability of any other laboratory to repeat the calibration. (A+A)\*L shall not be liable for any loss or damage resulting from the use of the equipment.

Certificate No.: APJ22-083-CC001



Page 3 of 3