

<u>Appendix E</u> <u>Noise Monitoring Equipment Calibration</u> <u>Certificate</u>

The copyright of this document is owned by Acuity Sustainability Consulting Limited. It may not be reproduced except with prior written approval from the Company.



CALIBRATION CERTIFICATE

Certificate Informat	tion				
Date of Issue	23-May-2022			Certificate Number	MLCN221167S
Customer Informati	on				
Company Name	server and a server and the server and the	ability Consulting Lin	nited		
Address		ord Glory Plaza,			
	Nos. 37-39 Win	ng Hong Street, an, Kowloon, HK			
		an, Kowioon, HK			
Equipment-under-T	est (EUT)				
Description	Sound Calibrato	or			
Manufacturer	Scarlet Tech				
Model Number	ST-120				
Serial Number	200504747				
Equipment Number					
Calibration Particul	ar	and the second s			
Date of Calibration	23-May-2022				
Calibration Equipment		3) / AV200063 / 23-Ju			
	1357(MLTE190) / MLEC21/05/02 /	26-May-22		
Calibration Procedure	MLCG00, MLC	C15			
	Lange and the second				
Calibration Conditions	Laboratory	Temperature	23 °C ± 5	0770	
	EUT	Relative Humidity Stabilizing Time	$55\% \pm 25\%$ Over 3 hor		
	LOI	Warm-up Time	Not applic		
		Power Supply	Internal ba		
Calibration Results	Calibration data	were detailed in the	Lease	the state of the s	
		were detailed in the t	continuation	pages.	
Approved By & Date					
			1	K.O. Lo	22 May 2022
Statements	Section and the section of the secti			N.O. LU	23-May-2022
* Calibration equipment used	for this calibration ar	re traceable to national / i	nternational st	andards	
 The results on this Calibration 	on Certificate only re	late to the values measure	ed at the time of	of the calibration and the un	certainties quoted will
not include allowance for the overloading, mishandling, m	e EUT long term drif	t, variation with environr	mental changes	, vibration and shock during	g transportation,
 * MaxLab Calibration Centre 	Limited shall not be	liable for any loss or dam	hage resulting f	rom the use of the EUT	
 The copy of this Certificate 	is owned by MaxLab	Calibration Centre Limi	ted. No part o	f this Certificate may be rep	roduced without the
prior written approval of Ma	xLab Calibration Ce	ntre Limited.		3	

Page 1 of 2



Certificate No. MLCN221167S

Calibration Data						
EUT Setting	Standard Reading	EUT Error from Setting	Calibration Uncertainty			
94 dB	95.3 dB	1.3 dB	0.15 dB			
114 dB	116.0 dB	2.0 dB	0.15 dB			

- END -

Calibrated By : Date : Dan

23-May-22

Checked By : Date :

23-May-22

K.O. Lo

Page 2 of 2



Certificate of Calibration

Acoustics and Air Testing Laboratory Co. Ltd. 聲學及空氣測試實驗室有限公司

for

Description:	Sound Level Meter
Manufacturer:	Scarlet Tech
Type No.:	ST11D (Serial No.: 820250)
Microphone:	BSWA 231 (Serial No.:590497)

Submitted by:

Customer: Acuity Sustainability Consulting Limited Address: Unit E, 12/F., Ford Glory Plaza, Nos. 37-39 Wing Hong Street, Cheung Sha Wan, Kowloon, Hong Kong

Upon receipt for calibration, the instrument was found to be:

the allowable tolerance.

(A+A)

The test equipment used for calibration are traceable to National Standards via:

- The Government of The Hong Kong Special Administrative Region Standard & Calibration Laboratory

Date of receipt: 05 October 2022

Date of calibration: 07 October 2022

Date of NEXT calibration: 06 October 2023

Calibrated by: Calibration Technician

Certified by:______

Mr. Ng Yan Wa Laboratory Manager

Page 1 of 3

Certificate No.: APJ22-083-CC001

Date of issue: 7 October 2022

Room 422,Leader Industrial Centre,57-59 Au Pui Wan Street ,Fo Tan, Shatin,N.T.,Hong Kong Tel: (852) 2668 3423 Fax:(852) 2668 6946 Homepage: http://www.aa-lab.com E-mail : inquiry@aa-lab.com

(A+A)*L Acoustics and Air Testing Laboratory Co. Ltd. 聲學及空氣測試實驗室有限公司

1. Calibration Precaution:

- The unit-under-test (UUT) was allowed to stabilize in the laboratory for over 24 hours, and switched on to warm up for over 10 minutes before the commencement of the test.
- The results presented are the mean of 3 measurements at each calibration point.

2. Calibration Conditions:

Air Temperature:	23.3 °C
Air Pressure:	1005 hPa
Relative Humidity:	57.6 %

3. Calibration Equipment:

	Туре	Serial No.	Calibration Report Number	Traceable to	
Multifunction Calibrator	B&K 4226	2288467	AV220061	HOKLAS	

4. Calibration Results

Sound Pressure Level

Reference Sound Pressure Level

Setting of Unit-under-test (UUT)			Applied value		UUT Reading,	IEC 61672 Class 1	
Range, dB	Freq. W	eighting	Time Weighting	Level, dB	Frequency, Hz	dB	Specification, dB
43-138	dBA	SPL	Fast	94	1000	94.3	±0.4

Linearity

Setting of Unit-under-test (UUT)				Арр	lied value	UUT Reading,	IEC 61672 Class 1
Range, dB	Freq. V	Weighting	Time Weighting	Level, dB	Frequency, Hz	dB	Specification, dB
				94		93.8	Ref
43-138	dBA	SPL	Fast	104	1000	104.2	±0.3
				114		114.3	±0.3

Time Weighting

Setting of Unit-under-test (UUT)			Appl	lied value	UUT Reading,	IEC 61672 Class 1	
Range, dB	Freq. W	eighting	Time Weighting	Level, dB	Frequency, Hz	dB	Specification, dB
42 129	JD A	CDI	Fast	04	1000	93.8	Ref
43-138 dBA SPL	Slow	94 1000	1000	94.3	±0.3		

Certificate No.: APJ22-083-CC001

Page 2 of 3

Room 422,Leader Industrial Centre,57-59 Au Pui Wan Street ,Fo Tan, Shatin,N.T.,Hong Kong Tel: (852) 2668 3423 Fax:(852) 2668 6946 Homepage: http://www.aa-lab.com E-mail : inquiry@aa-lab.com

(A+A)*L Acoustics and Air Testing Laboratory Co. Ltd. 聲學及空氣測試實驗室有限公司

Frequency Response

A-weighting

Sett	ing of Uni	it-under-t	est (UUT)	Appl	Applied value		IEC 61672 Class 1										
Range, dB	Freq. W	/eighting	Time Weighting	Level, dB	Frequency, Hz	dB	Specification, dB										
					31.5	56.2	-39.4 ±2.0										
							63	68.6	-26.2±1.5								
				125	78.3	-16.1±1.5											
42,120			Fast	Fast	Fast	Fast	Fast	Fast	Fast	Fast	Fast	Fast	The second se	0.1	250	85.8	-8.6±1.4
43-138	dBA	SPL											Fast 94	500	91.1	-3.2 ± 1.4	
											1000	94.3	Ref				
												2000	94.9	$+1.2\pm1.6$			
4					4000	93.5	$+1.0 \pm 1.6$										

5. Calibration Results Applied

The results apply to the particular unit-under-test only. All calibration points are within manufacture's specification as IEC 61672 Class 1.

94 dB	31.5 Hz	± 0.10
	63 Hz	± 0.15
	125 Hz	± 0.05
	250 Hz	± 0.10
	500 Hz	± 0.10
	1000 Hz	± 0.05
	2000 Hz	± 0.05
	4000 Hz	± 0.05
104 dB	1000 Hz	± 0.05
114 dB	1000 Hz	± 0.05

Uncertainties of Applied Value:

The uncertainties are evaluated for a 95% confidence level.

Note:

The values given in this certification only related to the values measured at the time of the calibration and any uncertainties quoted will not allow for the equipment long-term drift, variations with environmental changes, vibration and shock during transportation, overloading, mis-handling, or the capability of any other laboratory to repeat the calibration. (A+A)*L shall not be liable for any loss or damage resulting from the use of the equipment.

Certificate No.: APJ22-083-CC001



Page 3 of 3

Room 422,Leader Industrial Centre,57-59 Au Pui Wan Street ,Fo Tan, Shatin,N.T.,Hong Kong Tel: (852) 2668 3423 Fax:(852) 2668 6946 Homepage: http://www.aa-lab.com E-mail : inquiry@aa-lab.com